

STANDARD FEATURES

Adjust-a-Flex™ Mounting System • Precision precompressed adjustable mount • Rubber isolators for vibration-free performance • Versatile six-way adjustment for trouble-free installation • Unique rear mount system provides double support for added stability and strength • Self-adjusting to stringer surface

Multi-Port Fuel Injection • Instant starting • Precise throttle response • Outstanding cruising and top-end performance • Increased fuel efficiency • MEFI-4b™ is the latest technology by GM

Engine Management System • Knock sensor adjusts for low octane fuel

- Automatic spark advance provides peak performance in all operating conditions
- Monitors the vital signs of the lubrication and cooling systems
- Rev limiter prevents engine damage from over-revving

Exclusive Fuel Control Cell™ • Eliminates need for specially modified fuel tank for EFI installations • Eliminates vapor lock • Protects EFI system against contaminated fuel • Premium, extra large fuel filter/water separator

- Easy to reach and service

Lubrication System • Full pressure full flow filtering system

- Positive crankcase ventilation • Remote oil filter for easy maintenance

Cooling System • Freshwater cooling (optional on 5.0/5.7) • Transmission cooler • High volume stainless steel modular raw water pump • Thermosyphon controlled cooling system

Exhaust System • Free breathing pyramidal exhaust manifold • High level exhaust discharge • Reversible exhaust riser system

Electrical System • Electronic Ignition • 12-volt negative ground system

- High output 100-amp alternator • Overload damage protection by a manual reset circuit breaker • Prewired wiring harness with eight-prong disconnect • High-torque positive-engagement top-mount marine starter • Temperature, oil pressure and voltage sending unit • Moisture cover

Transmissions Options • PCM Power Plus® in direct drive or 1.23:1 reduction gear • In-line and V-drives • New! Power Plus Vee, the ultimate in vee-drive transmissions

Miscellaneous • Owner's manual • Engine lifting rings • Throttle and shift control brackets • Multi-coat non-corrosive paint protection • U.S. Coast Guard approved flame arrester

Warranty • 3-year limited warranty

©Pleasurecraft Engine Group. We reserve the right to change specs or products without incurring obligation. *Power rated at the crankshaft in accordance with NMMA procedure **With 1:1 in-line transmission.



Model: ZR-6 6L
Rated Power: * 375 @ 5200 rpm
Fuel System: Multi-Port Fuel Injection
Length: 40.51" Width: 27.6"
Height: 22.27" Weight: ** 930 lbs



Model: Excalibur 330
Rated Power: * 330 @ 5000 rpm
Fuel System: Multi-Port Fuel Injection
Length: 44.1" Width: 27.8"
Height: 20.9" Weight: ** 950 lbs



Model: ProSport 5.0L
Rated Power: * 275 @ 5000 rpm
Fuel System: Multi-Port Fuel Injection
Length: 44.1" Width: 27.8"
Height: 20.9" Weight: ** 950 lbs